


OUTDOOR RENDER



PRODUCT NAME	CLINK' OUTSIDE
STANDARD	UNE - EN 998-1
COMPOSITION	Grey/white cement-based mortar, resin and mineral filler.
DESCRIPTION	CLINK' OUTSIDE is a mortar for the outdoor rendering of brick or concrete block surfaces. Available in grey or white.



OUTDOOR RENDER

CLINK' OUTSIDE

METHOD OF APPLICATION

PREPARATION:

- Ensure the surfaces to be tiled are in good condition, clean, and that there are no traces of grease or dust.
- Do not apply to plaster, old paint or any other surfaces that it will not adhere to correctly.

PRODUCT PREPARATION:

- Sprinkle CLINK' OUTSIDE into the correct amount of clean water for the quantity of product to be mixed. Do not use more than the recommended amount of water.
- Leave the mixture to stand for a few minutes.
- Mix by hand or with an electric mixer (on a low setting), until you have a smooth, even mixture with no lumps.

APPLICATION:

- Apply CLINK' OUTSIDE to the surface thickly and evenly. Next, use a rule or a trowel to spread it out evenly over the surface.
- When the render is hard enough, you can create the desired finish (screed, scraping or stippling).
- The thickness of each coat should be between 12 and 15 mm.



ADVANTAGES

High yield

Plane-defect repair

Decorative finish

TECHNICAL DATA

CONSISTENCY:	175 ± 10 mm
WATER FOR CONSISTENCY 175± 10:	20 - 22 %
CAPILLARY WATER ABSORPTION:	W1
YIELD:	14-15 kg / m ²
REACTION TO FIRE:	Clase A1
APPLICATION TEMPERATURE:	5 °C - 40 °C

PACKAGING



20 KG/SACK



64 SACKS/PALLET



25 TN



STORAGE AND PRESERVATION

- Store the product on a flat surface and never outdoors. Keep dry and out of direct sunlight.
- Use within 12 months of the date of manufacture.

LEGAL NOTICE: This information, in particular the recommendations relating to product application and the technical data, is based on our experience and current knowledge as well as the suggested uses and common applications of our products, and is subject to the final conditions of the site or the application of the products. GYPROD is not liable for the use of the products by third parties, or for the results obtained.
The GYPROD quality guarantee is limited exclusively to the product supplied.