

REPAIR MORTAR



PRODUCT NAME	CLINK' REPAIR
STANDARD	UNE – EN 1504
COMPOSITION	Cement-based powdered render with sand, resin and various additives.
DESCRIPTION	Repair render for indoor and outdoor use. Non-contracting and highly adhesive. • Fills: holes and cracks, joints between bricks, aerated concrete, plaster. • Repairs: ledges, window frames. • Renders: façades, cement coat, ashlar, etc.





REPAIR MORTAR

CLINK' REPAIR

METHOD OF APPLICATION

PREPARATION:

- Surfaces must be clean, dry and free from dust and any traces of mould-release oil.
- It is essential that the surfaces are very cohesive.

PRODUCT PREPARATION:

- Sprinkle CLINK' REPAIR into clean water and mix until you have a smooth, even paste without lumps.

APPLICATION:

- The thickness recommended for each coat is approximately 2 cm.
- When it is completely dry, the render can be covered with any type of paint, plaster render, adhesive cement, etc.
- **Precautions:** do not use on plaster or old paint. Do not use the mortar if it has started to set, and do not apply it to floors.



ADVANTAGES

High yield

Excellent adhesion

Can be used with all types of covering materials

TECHNICAL DATA

SETTING STARTS AT:	40min
SETTING FINISHED AT:	1H 30 min
DRYING TIME:	12H
APPLICATION TEMPERATURE:	5 °C - 40 °C

PACKAGING



20 KG/SACK



64 SACKS/PALLET



25 TN



STORAGE AND PRESERVATION

- Store the product on a flat surface and never outdoors. Keep dry and out of direct sunlight.
- Use within 12 months of the date of manufacture.

LEGAL NOTICE: This information, in particular the recommendations relating to product application and the technical data, is based on our experience and current knowledge as well as the suggested uses and common applications of our products, and is subject to the final conditions of the site or the application of the products. GYPROD is not liable for the use of the products by third parties, or for the results obtained.
The GYPROD quality guarantee is limited exclusively to the product supplied.