

CLAY-BRICK ADHESIVE

**PRODUCT NAME**

CLINK' STRONG

STANDARD

UNE – EN 12004

COMPOSITION

Cement, sand, resin and various additives.

DESCRIPTION

CLINK' STRONG is a cement-based powder adhesive for erecting terracotta brick walls. Adapted for wet areas such as showers, bathrooms, toilets, kitchens, etc.





CLAY-BRICK ADHESIVE

CLINK' STRONG

METHOD OF APPLICATION

PREPARATION:

- The bricks must be dry and free from dust.
- The floors that the first rows will be laid on must also be dry. A damp-proof course to protect against rising damp will also be needed.

PRODUCT PREPARATION:

- Sprinkle CLINK' STRONG into clean water and mix until you have a smooth, even paste.

APPLICATION:

- Apply the adhesive to the edges of the bricks. The joints should be about 2mm wide.
- Lay the bricks spacing the joints correctly. The gap between the last row of bricks and the ceiling must be as small as possible.
- Fix the wall with adhesive cement.



ADVANTAGES

High yield

Quick-setting

Waterproof

TECHNICAL DATA

SETTING TIME:	1H
DRYING TIME:	2 - 3H
APPLICATION TEMPERATURE:	5 °C - 40 °C
MAXIMUM AGGREGATE SIZE:	< 1 mm

PACKAGING



20 KG/SACK



64 SACKS/PALLET



25 TN



STORAGE AND PRESERVATION

- Store the product on a flat surface and never outdoors. Keep dry and out of direct sunlight.
- Use within 12 months of the date of manufacture.

LEGAL NOTICE: This information, in particular the recommendations relating to product application and the technical data, is based on our experience and current knowledge as well as the suggested uses and common applications of our products, and is subject to the final conditions of the site or the application of the products. GYPROD is not liable for the use of the products by third parties, or for the results obtained.
The GYPROD quality guarantee is limited exclusively to the product supplied.