

NO-TAPE JOINT PLASTER

**PRODUCT NAME**

GYPS' JOINT WITHOUT

STANDARD

UNE - EN 13963

DESCRIPTION

GYPS' JOINT WITHOUT is a fast-setting plaster for treating and finishing joints WITHOUT the use of paper tape:

- Plasterboard.
- Treating fibreboard joints.





NO-TAPE JOINT PLASTER

GYPS' JOINT WITHOUT

METHOD OF APPLICATION

PREPARATION:

- The surface must be absorbent.
- The surfaces must be clean, dry and free of dust and other elements. Remove any dust from the joints between the boards.

PRODUCT PREPARATION:

- Sprinkle GYPS' JOINT WITHOUT into clean water.
- Leave it to stand for around 2-3 minutes to let the plaster hydrate correctly.
- Mix vigorously, either manually or mechanically, until you have a good consistency.

APPLICATION:

- Use a spatula or trowel to deeply fill the joints and tapered areas, and going over the edges by 3 to 5 cm. After approximately 1h 30, apply another coat to smooth it out and finish the joint.
- When completely dry, the render can be covered with any type of paint, plaster-based render, putty, wallpaper, etc.

ADVANTAGES

All-purpose product

Easy glide

No shrinkage



TECHNICAL DATA

USE WITHIN:	2 H
DRYING TIME:	6 H
WATER-PRODUCT RATIO:	12 - 15 l/sack
APPLICATION TEMPERATURE:	5 °C - 40 °C

PACKAGING



25 KG/SACK



48 SACKS/PALLET



25 TN



STORAGE AND PRESERVATION

- Store the product on a flat surface and never outdoors. Keep dry and out of direct sunlight.
- Use within 12 months of the date of manufacture.

LEGAL NOTICE: This information, in particular the recommendations relating to product application and the technical data, is based on our experience and current knowledge as well as the suggested uses and common applications of our products, and is subject to the final conditions of the site or the application of the products. GYPROD is not liable for the use of the products by third parties, or for the results obtained.
The GYPROD quality guarantee is limited exclusively to the product supplied.