

ALL-PURPOSE PLASTER

**PRODUCT NAME**

GYPS' ALL

STANDARD

UNE - EN 13963

DESCRIPTION

GYPS' ALL is a product that can be used for bonding cladding panels, as well as joining boards, and providing a surface finish. It is specially designed to be used with plasterboard.

ALL-PURPOSE PLASTER

GYPS' ALL

METHOD OF APPLICATION

PREPARATION:

- The surface should be free of dust, particles, efflorescence, mould release oil and other residue that may adversely affect the adhesion of the coating. Clean the surface before use if you consider it necessary.

PRODUCT PREPARATION:

- Sprinkle GYPS' ALL into clean water.
- Leave it to stand for around 2-3 minutes to let the plaster hydrate correctly.
- Mix vigorously, either manually or mechanically, until you have a good consistency.

APPLICATION:

- **Sticking plasterboard:** Apply the plaster to the board in blobs around 10 cm in diameter. When sticking boards with fibre insulation, we recommend you smooth the surface first and then apply the blobs of plaster.
- **Jointing:** Fill the joints and tapered areas. Put the tape over the joint and 'iron' it out with a spatula. Once dry, cover the band again, this time spreading the plaster 3 to 5 cm outside the joint.
- **Sanding, filling and finishing work:** Directly onto construction materials.



ADVANTAGES

All-purpose product

Strong bond

No shrinkage

TECHNICAL DATA

USE WITHIN:	2 H
DRYING TIME:	6 H
WATER-PRODUCT RATIO:	7 - 8 l/sack
APPLICATION TEMPERATURE:	5 °C - 40 °C

PACKAGING



25 KG/SACK



48 SACKS/PALLET



25 TN



STORAGE AND PRESERVATION

- Store the product on a flat surface and never outdoors. Keep dry and out of direct sunlight.
- Use within 12 months of the date of manufacture.

LEGAL NOTICE: This information, in particular the recommendations relating to product application and the technical data, is based on our experience and current knowledge as well as the suggested uses and common applications of our products, and is subject to the final conditions of the site or the application of the products. GYPROD is not liable for the use of the products by third parties, or for the results obtained.
The GYPROD quality guarantee is limited exclusively to the product supplied.