

PLASTER-PARTITION ADHESIVE

**PRODUCT NAME**

GYPS' STRONG PLASTER ELEMENTS FIXING

STANDARD

UNE - EN 12860

DESCRIPTION

GYPS' STRONG PLASTER ELEMENTS FIXING is an adhesive product created for erecting and rendering indoor plaster partitions.

Its special formula ensures maximum yield for the installation of your partition.

One of its qualities is that there is no shrinkage, resulting in an excellent finish.





PLASTER-PARTITION ADHESIVE

GYPS' STRONG PLASTER ELEMENTS FIXING

METHOD OF APPLICATION

PREPARATION:

- The surface to be finished should be free of dust, particles, efflorescence, mould release oil and other residue that may adversely affect the adhesion of the coating. Clean the surface before use if you consider it necessary.

PRODUCT PREPARATION:

- Sprinkle GYPS' STRONG PLASTER ELEMENTS FIXING into the correct amount of clean water for the quantity of product to be mixed.
- Leave it to stand for around 2 minutes to let the plaster hydrate correctly.
- Mix with a mixing drill until you have a smooth, even paste.

APPLICATION:

- Use a spatula to apply the product to the surface to be stuck in an even layer or line.
- Put the component into place, pressing on it so that the plaster runs into the joints.
- Finish off the joints and contact points.

ADVANTAGES

Simple application

High yield

Excellent quality finish

Excellent adhesion

Excellent mechanical properties



TECHNICAL DATA

SETTING TIME:	2H
DRYING TIME:	5/6H
WATER / PRODUCT RATIO:	10 - 11 l/sack
APPLICATION TEMPERATURE:	5 °C - 40 °C

PACKAGING



25 KG/SACK



48 SACKS/PALLET



25 TN



STORAGE AND PRESERVATION

- Store the product on a flat surface and never outdoors. Keep dry and out of direct sunlight.
- Use within 12 months of the date of manufacture.

LEGAL NOTICE: This information, in particular the recommendations relating to product application and the technical data, is based on our experience and current knowledge as well as the suggested uses and common applications of our products, and is subject to the final conditions of the site or the application of the products. GYPROD is not liable for the use of the products by third parties, or for the results obtained. The GYPROD quality guarantee is limited exclusively to the product supplied.