

CLAY-BRICK-PARTITION ADHESIVE

**PRODUCT NAME**

GYPS' STRONG CLAY ELEMENTS FIXING

STANDARD

UNE - EN 12860

DESCRIPTION

GYPS' STRONG CLAY ELEMENTS FIXING is a plaster-based adhesive product for erecting terracotta brick partitions in dry indoor areas.





CLAY-BRICK-PARTITION ADHESIVE

GYPS' STRONG CLAY ELEMENTS FIXING

METHOD OF APPLICATION

PREPARATION:

- The surface should be free of dust, particles, efflorescence, mould release oil and other residue that may adversely affect adhesion. Clean the surface before use if you consider it necessary.

PRODUCT PREPARATION:

- Sprinkle GYPS' STRONG CLAY ELEMENTS FIXING into the correct amount of clean water for the quantity of product to be mixed.
- Leave it to stand for 3-5 minutes to let the plaster hydrate correctly.
- Mix mechanically until you have a good consistency.

APPLICATION:

- Apply the adhesive to the edge of the partition in an even layer or line.
- Put the brick component into place, pressing on it so that the plaster squeezes out.
- Finish off the joints and contact points.

ADVANTAGES

Simple application

Excellent adhesion

High yield



TECHNICAL DATA

SETTING TIME:	2H
DRYING TIME:	4-5H
MIXTURE STANDING TIME:	3-5 min
WATER / PRODUCT RATIO:	12 - 13 l/sack
APPLICATION TEMPERATURE:	5 °C - 40 °C

PACKAGING



25 KG/SACK



48 SACKS/PALLET



25 TN



STORAGE AND PRESERVATION

- Store the product on a flat surface and never outdoors. Keep dry and out of direct sunlight.
- Use within 12 months of the date of manufacture.

LEGAL NOTICE: This information, in particular the recommendations relating to product application and the technical data, is based on our experience and current knowledge as well as the suggested uses and common applications of our products, and is subject to the final conditions of the site or the application of the products. GYPROD is not liable for the use of the products by third parties, or for the results obtained. The GYPROD quality guarantee is limited exclusively to the product supplied.