

MANUAL CONTROLLED PLASTER

**PRODUCT NAME**

GYPS' PLASTER DELAYED SET TIME MANUAL

STANDARD

UNE - EN 13279-1

DESCRIPTION

GYPS' PLASTER DELAYED SET TIME MANUAL is a thick granulometry building plaster with a controlled set time for manual application, to be used for indoor finishing coats. It is also known as controlled plaster.





MANUAL CONTROLLED PLASTER

GYPS' PLASTER DELAYED SET TIME MANUAL

METHOD OF APPLICATION

PREPARATION:

- The surfaces to be plastered must be a plane, so any rough parts or lumps should be eliminated and dips and holes should be filled.
- In the case of excessively flat surfaces, apply a mechanical treatment to provide a certain amount of roughness and help the mechanical adhesion of the coat.
- The surface should be free of dust, particles, efflorescence, mould release oil and other residue that may adversely affect the adhesion of the coat. Clean the surface before use if you consider it necessary.

PRODUCT PREPARATION AND APPLICATION:

- Sprinkle GYPS' PLASTER DELAYED SET TIME MANUAL into clean water until it stops becoming wet.
- Mix mechanically until you get a smooth plaster.
- Use the float to apply the plaster to the surface until you have the desired thickness.

ADVANTAGES

Simple application

High yield

Excellent mechanical properties

Humidity regulation



TECHNICAL DATA

USE WITHIN:	13-15 min
MIXTURE STANDNG TIME:	5-10 min
FINISHING TIME	30-40 min
WATER / PRODUCT RATIO:	17 - 18 l/sack
APPLICATION TEMPERATURE:	5 °C - 40 °C

PACKAGING



25 KG/SACK



48 SACKS/PALLET



25 TN



STORAGE AND PRESERVATION

- Store the product on a flat surface and never outdoors. Keep dry and out of direct sunlight.
- Use within 12 months of the date of manufacture.

LEGAL NOTICE: This information, in particular the recommendations relating to product application and the technical data, is based on our experience and current knowledge as well as the suggested uses and common applications of our products, and is subject to the final conditions of the site or the application of the products. GYPROD is not liable for the use of the products by third parties, or for the results obtained.
The GYPROD quality guarantee is limited exclusively to the product supplied.